

TITLE OF THE INVENTION
PRINT CONTROL APPARATUS AND METHOD

FIELD OF THE INVENTION

5 The present invention relates to a print control
apparatus such as a host computer or the like connected
to a printer, which performs setups of parameters that
control a printer, maintenance of tables which are used
to correct and convert an image output form the printer,
10 and the like, and a print control method.

BACKGROUND OF THE INVENTION

 When an image composited by a personal computer or
the like is output by a printer, a print control
15 apparatus implemented by a personal computer must
color-convert image data expressed by luminance signals
R (red), G (green), and B (blue) into color signals Y
(yellow), M (magenta), C (cyan), and K (black) (or Y, M,
C) used in the printer. In this conversion, color
20 correction of RGB data (from 8-bit RGB data into 8-bit
RGB data), color conversion (from 8-bit RGB data into
8-bit CMYK data), grayscale correction (from 8-bit CMYK
data to 8-bit CMYK data), and quantization (from 8-bit
CMYK data into 1-bit CMYK data) are executed in turn.

25 Such conversion or correction uses look-up tables
prepared in advance. Each processing module that

00597403-002400

implements conversion or correction holds its look-up
tables, and retrieves and loads a look-up table
according to a print mode designated by print quality, a
quantization method, and the like in its own search
5 sequence to execute relevant processes.

That is, it is a common practice to access a
conventional look-up table inside a library module as a
part of the library module that attains correction or
conversion for image processes. Also, a table search
10 method is often unique to the library module.

The look-up tables prepared in advance differ only
in units of print modes. If a given print mode is
selected, identical printer models use an identical
look-up table regardless of their various head or
15 printer conditions.

However, since each module holds its own look-up
tables, when a print mode is added, deleted, or modified,
all modules must undergo addition, deletion, and
modification of look-up tables in correspondence with
20 the changed print mode to maintain consistency. If one
of these modules suffers errors, a normal print process
is often disturbed.

That is, in the conventional architecture in which
each library module accesses its own look-up tables,
25 even when only a look-up table has been changed, the
library module must be re-compiled every time the

look-up table is changed, resulting in, e.g., low debugging efficiency in the development process. Also, in a printer driver composed of a plurality of library modules which are created in units of functions, a

- 5 change in look-up table often influences a plurality of library modules, resulting in not only low efficiency but also low quality of the printer driver (first problem).

10 In the above method, look-up tables are prepared in advance, and identical printer models use an identical look-up table (LUT) independently of their head conditions and the like. Also, different LUTs are prepared only in units of print modes.

15 However, a single look-up table prepared in advance cannot always provide the best print results due to individual differences, aging, and the like of printer main bodies, ink heads, and the like. For example, when a magenta-rich head is used, the image is entirely tinged with red, or gray balance cannot be held
20 (second problem). In order to solve this problem, the look-up table must be updated, but updating of the look-up table poses the first problem.

When a print process is done using a print apparatus which can select a plurality of types of print
25 paper, various print methods, and the like, the user

selects or inputs various kinds of information required for an intended print process.

In this case, a print control apparatus displays setup values of print information required for the print process, e.g., setup items "ink cartridge", "paper type", "paper source", "grayscale print", "print quality", "dithering", "image data correction", "photo data correction", and the like, as shown in Fig. 32. The user selects or inputs setup values from the displayed items.

After setup values are input, the print control apparatus combines the selected or input information to obtain information required for the print process.

However, with this method, since the user must select or input various kinds of information required for the print process, the load on the user is heavy. Also, when the user inputs or selects wrong information, an optimal print process may be disturbed.

For example, when the user selects "OHP paper" as a setup value of setup item "paper type" but selects "auto sheet feeder" as a setup value of setup item "paper source" upon printing on paper for which "manual feed" must be selected as "paper source", a print error such as paper jam or the like is highly likely to occur since manual feed is not done. When the contents and the number of items of input information have been changed, or when the contents and the number of items of

09597403-062100

However, with this method, when an original condition or link information has been changed, combinations of search conditions must be re-defined. Since the combinations of conditions are statically defined by a mechanism for searching link information, the mechanism for searching link information, e.g., a program executed by a computer to search link information, must be changed upon re-defining conditions (third problem).

10 The conventional print control apparatus offers print margin information to an application program. Print margins offered by the print control apparatus are information required for reliably forming an image on a designated paper sheet, and differ depending on paper sizes, unlike margins set by an application or the like. 15 The print control apparatus computes the left margin, top margin, and vertical and horizontal printable area values on the basis of the vertical and horizontal sizes of a paper sheet, paper size name, or the like as an input, and offers them to the application. For example, 20 when the paper sheet has an A4 size, the left margin is 3.4 mm; when the paper sheet has an envelope size, it is 6.4 mm. When the paper sheet has a user-defined size, the print control apparatus computes margins using a 25 predetermined formula on the basis of the defined paper size.

With such conventional method, since the margin information computation processing sequence is coded as a program, when the number of types of paper sizes increases, the program must be updated in correspondence
5 with the sizes.

Furthermore, since printable paper sizes vary depending on printer models, the margin computation program must be developed in units of printer models. Moreover, the margin computation method changes not only
10 by paper sizes but also under complicated conditions to cope with continuous paper without top and bottom margins, perforated paper, and the like. As a result, a margin computation program including complicated condition checking steps must be developed in
15 correspondence with printer models.

In this manner, a development efficiency drop of a margin information offering system, and quality drop due to a complicated program readily occur (fourth problem).

As described in the first to fourth problems, when
20 the print control apparatus acquires data by searching a table, and executes predetermined operation on the basis of the acquired data, if the number of items of the table is changed, not only the table must be updated, but also a module (e.g., a program) that looks up the
25 table must be renewed.

SUMMARY OF THE INVENTION

09597403-062100
The present invention has been made in consideration of the aforementioned prior art, and has as its first object to provide a print control apparatus
5 and method which use data acquired by searching a table, wherein even when the number of items of a table has been changed, the table alone need only be changed, but modules that look up the table need not be changed.

It is another object of the present invention to
10 solve the first problem. That is, it is the second object of the present invention to provide a print control apparatus and method which allow easy maintenance of a look-up table independently of processes using the table, and can prevent consistency
15 among modules that use the look-up table from impairing.

It is still another object of the present invention to solve the second problem. That is, it is the third object of the present invention to provide a print control apparatus and method which can always
20 obtain satisfactory print results by generating a database including a look-up table in accordance with individual differences or aging of the characteristics of an output apparatus.

It is still another object of the present
25 invention to solve the third problem. That is, it is the fourth object of the present invention to provide a

print control apparatus and method which can form a high-quality image by generating and managing a look-up table itself in accordance with individual differences or aging of the characteristics of a print apparatus.

5 It is still another object of the present invention to solve the fourth problem. That is, it is the fifth object of the present invention to provide a print control apparatus and method which can link various functions of a print apparatus, can provide an optimal combination of functions, and can obviate the need for changing a search module even a search condition for the combined information has been changed.

10 In order to achieve the above objects, the present invention comprises the following arrangement. That is, a print control apparatus comprises:

 a first table for storing search conditions;

 a second table for storing data of values corresponding to the search conditions;

 search means for searching the first table for the search condition on the basis of a given condition, and searching the second table for data of a value corresponding to the acquired search condition; and

 table maintenance means for, when a given search condition has been changed, changing the search conditions stored in the first table, and changing a

value which is stored in the second table and corresponds to the changed search condition.

The print control apparatus preferably further comprises correction means for correcting an image, the
5 search means searches the first and second tables for a look-up table for image correction, and the correction means corrects the image with reference to the look-up table.

The print control apparatus preferably further
10 comprises setting means for setting print setup values, the search means searches the first and second tables for an appropriate combination of the print setup values, and the setting means prompts the user to input setup values with reference to the appropriate combination.

15 The print control apparatus preferably further comprises margin setting means for setting a print margin, the search means searches the first and second tables for an appropriate print margin, and the margin setting means offers the appropriate print margin to the
20 user.

Alternatively, there is provided a database comprising:

a first table for storing keys and look-up table identifiers in correspondence with each other; and

a second table for storing the look-up table identifiers and look-up tables in correspondence with each other,

wherein the look-up table can be searched via the
5 look-up table identifier corresponding to the designated key.

Alternatively, there is provided a print control apparatus comprising:

a first table for storing look-up table
10 identifiers used in image data conversion in correspondence with keys that use print modes;

a second table for storing look-up tables corresponding to the look-up table identifiers stored in the first table;

15 search means for searching the first table for a look-up table identifier corresponding to a designated print mode;

table acquisition means for acquiring a look-up table corresponding to the look-up table identifier
20 acquired by the search means from the second table; and

image processing means for processing image data using the acquired look-up table.

Alternatively, there is provided a print control method using a first table for storing look-up table
25 identifiers used in image data conversion in correspondence with keys that use print modes, and a

second table for storing look-up tables corresponding to the look-up table identifiers stored in the first table, comprising:

the search step of searching the first table for a
5 look-up table identifier corresponding to a designated print mode;

the table acquisition step of acquiring a look-up table corresponding to the look-up table identifier acquired in the search step from the second table; and
10 the image processing step of processing image data using the acquired look-up table.

Alternatively, there is provided a computer readable storage medium storing a computer program which makes a computer implement:

15 search means for searching a first table for storing look-up table identifiers used in image data conversion in correspondence with keys that use print modes for a look-up table identifier corresponding to a designated print mode;

20 table acquisition means for acquiring a look-up table corresponding to the look-up table identifier acquired by the search means from a second table for storing look-up tables corresponding to the look-up table identifiers stored in the first table; and

25 image processing means for processing image data using the acquired look-up table.

Alternatively, there is provided an information processing apparatus comprising:

a processing module; and

a database corresponding to a given apparatus,

5 wherein the processing module has a search unit in which information used to access the database corresponding to the selected apparatus is set.

Alternatively, there is provided a printer driver comprising:

10 a processing module; and

a database corresponding to a printer,

wherein the processing module has a search unit in which information used to access the database corresponding to the selected printer is set.

15 Alternatively, there is provided a print control apparatus for executing an image process in accordance with an output apparatus, comprising:

generation means for generating a look-up table according to characteristic information of the output
20 apparatus;

storage means for storing the generated look-up table in correspondence with an identifier of the output apparatus; and

image processing means for executing a process
25 such as correction, conversion, or the like for image

data using the look-up table corresponding to the identifier.

Alternatively, there is provided a print control method for executing an image process in accordance with
5 an output apparatus, comprising:

the generation step of generating a look-up table according to characteristic information of the output apparatus;

the storage step of storing the generated look-up
10 table in correspondence with an identifier of the output apparatus; and

the image processing step of executing a process such as correction, conversion, or the like for image data using the look-up table corresponding to the
15 identifier.

Alternatively, there is provided a link information search apparatus comprising:

changed value storage means for storing changed information;

20 current value storage means for storing unchanged information;

link information storage means for storing link information required for optimizing the unchanged information upon the change;

reference information determination means for determining link information to be referred to for the optimization;

5 extraction condition setting means for setting a condition required for extracting link information from the link information storage means; and

setup value information replace means for updating information stored in the current value storage means on the basis of the extracted link information.

10 Alternatively, there is provided a link information search method comprising:

the changed value storage step of storing changed information in a first memory;

15 the current value storage step of storing unchanged information in a second memory;

the link information storage step of storing in a third memory link information required for optimizing the unchanged information upon the change;

20 the reference information determination step of determining link information to be referred to for the optimization;

the extraction condition setting step of setting a condition required for extracting link information stored in the third memory; and

the setup value information replace step of updating information stored in the second memory on the basis of the extracted link information.

Alternatively, there is provided a computer
5 readable storage medium storing a program for searching for and updating link information to optimize unchanged information upon changing information, the program comprising:

a code of the changed value storage step of
10 storing changed information in a first memory;

a code of the current value storage step of storing unchanged information in a second memory;

a code of the link information storage step of storing in a third memory link information required for
15 optimizing the unchanged information upon the change;

a code of the reference information determination step of determining link information to be referred to for the optimization;

a code of the extraction condition setting step of
20 setting a condition required for extracting link information stored in the third memory; and

a code of the setup value information replace step of updating information stored in the second memory on the basis of the extracted link information.

25 Alternatively, there is provided a link information setting apparatus comprising:

acquisition means for acquiring an ID of a link
information storage section corresponding to a changed
item;

setting means for setting an extraction condition
5 of the link information storage section having the
acquired ID;

extraction means for extracting link information
from the link information storage section having the
acquired ID in accordance with the set extraction
10 condition; and

change means for changing a setup value when the
setup value is different from the extracted link
information.

Alternatively, there is provided a link
15 information setting method comprising:

the acquisition step of acquiring an ID of a link
information storage section corresponding to a changed
item;

the setting step of setting an extraction
20 condition of the link information storage section having
the acquired ID;

the extraction step of extracting link information
from the link information storage section having the
acquired ID in accordance with the set extraction
25 condition; and

the change step of changing a setup value when the setup value is different from the extracted link information.

Alternatively, there is provided a storage medium
5 storing a program code for making computer execute a link information setting method, the program code comprising:

a code of the acquisition step of acquiring an ID of a link information storage section corresponding to a
10 changed item;

a code of the setting step of setting an extraction condition of the link information storage section having the acquired ID;

a code of the extraction step of extracting link
15 information from the link information storage section having the acquired ID in accordance with the set extraction condition; and

a code of the change step of changing a setup value when the setup value is different from the
20 extracted link information.

Alternatively, there is provided a print control apparatus comprising:

storage means for storing identification information for identifying print conditions, and paper
25 size-dependent parameters based on the identification information; and

margin information generation means for searching for the stored identification information and parameters in accordance with print information, and generating corresponding margin information.

5 Alternatively, there is provided a print control method comprising:

the storage step of storing in a memory identification information for identifying print conditions, and paper size-dependent parameters based on
10 the identification information; and

the margin information generation step of searching for the stored identification information and parameters stored in the memory in accordance with print information, and generating corresponding margin
15 information.

Alternatively, there is provided a storage medium storing a program for offering margin information for print control, the program comprising:

a code of the storage step of storing in a memory identification information for identifying print
20 conditions, and paper size-dependent parameters based on the identification information; and

a code of the margin information generation step of searching for the stored identification information
25 and parameters stored in the memory in accordance with

print information, and generating corresponding margin information.

Other features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

Fig. 1 is a block diagram showing the arrangement of an image processing system according to the first embodiment of the present invention;

Fig. 2 shows the relationship between a database file and color correction/color conversion module;

Fig. 3 shows the relationship between a database file and grayscale correction/quantization module;

Fig. 4 is a view showing the concept of a plurality of tables LUT1;

Fig. 5 is a view showing actual color correction/color conversion tables of a plurality of tables LUT2;

Fig. 6 is a view showing actual grayscale correction/dither matrix tables of the plurality of tables LUT2;

Fig. 7 is a flow chart of a print process sequence;

Fig. 8 is a flow chart of a color correction/color conversion process;

Fig. 9 is a flow chart of a grayscale correction/quantization process;

Fig. 10 is a flow chart of a table ID search process;

Fig. 11 is a view showing actual color correction/color conversion tables of the plurality of tables LUT2, the contents of which have changed;

Fig. 12 shows the relationship between a database file and database maintenance module;

Fig. 13 is a flow chart of a database maintenance process;

Fig. 14 is a schematic block diagram showing an example of the arrangement of a printer driver according to the second embodiment of the present invention;

Fig. 15 is a schematic block diagram showing an example of the arrangement of an image processing module;

Fig. 16 is a perspective view showing the structure of an ink-jet printer;

Fig. 17 is a block diagram of software modules for a print process;

Fig. 18 is a block diagram of a computer system which is used to implement the present invention;

5 Fig. 19 is a block diagram showing the arrangement of an image processing system as an embodiment of a data conversion apparatus according to the present invention;

Fig. 20 is a diagram showing the concept upon generating a new database file;

10 Fig. 21 is a diagram showing the concept upon editing a database file;

Fig. 22 shows the architecture of a database file;

Fig. 23 is a graph showing the adjustment results of an LUT of a grayscale correction table in accordance
15 with head ranks;

Fig. 24 is a view showing the database file names corresponding to head IDs;

Fig. 25 is a flow chart showing a calibration sequence by a driver module;

20 Fig. 26 is a flow chart showing a calibration sequence by a calibration module;

Fig. 27 is a flow chart showing a print sequence by the driver module;

Fig. 28 is a block diagram showing the concept
25 when a print destination port is a printer in the third embodiment;

Fig. 29 is a block diagram showing the concept when a print destination port is a file in the third embodiment;

Fig. 30 is a flow chart showing a print sequence
5 in the third embodiment;

Fig. 31 is a schematic block diagram of a system which comprises a link information search apparatus as an embodiment of the present invention, a display apparatus, and an input unit;

Fig. 32 shows a display window that pertains to setups of a printer driver as an embodiment of the
10 present invention;

Fig. 33 shows an example of changed item and setup value information;

Fig. 34 shows an example of data stored in a
15 current value storage unit;

Fig. 35 shows the IDs and their contents in a link information storage unit;

Fig. 36 shows an example of extraction conditions
20 set in units of IDs;

Fig. 37 shows an example of list data of IDs of the link information storage unit, which must be referred to;

Fig. 38 is a flow chart for explaining a link
25 information change process;

00597403.002400
007200.007550

Fig. 39 is a flow chart for explaining link information acquisition;

Fig. 40 shows an example of the contents of link information storage section 1 (reference media
5 correction table);

Fig. 41 shows an example of the contents of link information storage section 2 (medium correspondence table);

Fig. 42 shows an example of the contents of link
10 information storage section 3 (grayscale correspondence table);

Fig. 43 shows an example of the contents of link information storage section 4 (quality - level correspondence table);

15 Fig. 44 shows an example of the contents of link information storage section 5 (quality message - binarization method correspondence table);

Fig. 45 shows an example of the contents of link information storage section 6 (resolution correspondence
20 table);

Fig. 46 shows an example of link information stored in an extracted information storage unit;

Fig. 47 shows the setup window of a printer driver that has reflected link information after a series of
25 processes;

Fig. 48 is a block diagram for explaining the system arrangement;

Fig. 49 is a flow chart showing a margin information offering process;

5 Fig. 50 shows the structure of an index table;

Figs. 51A to 51C show an example of the structures of data tables of respective table IDs; and

Fig. 52 is a view for explaining margin information.

10

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Prior to a detailed description of the embodiments, an outline of each embodiment will be explained first. First and Second Embodiments (Figs. 1 to 18)

15

An LUT used in conversion, color correction, and the like of an image in a printer driver is a table independent of a conversion unit, and maintenance of that table is made by an independent maintenance module.

20

Furthermore, the table is divided into LUT1 that includes tables IDs corresponding to print modes, and LUT2 including actual tables for correction and conversion. By updating LUT2, the contents of a database can be updated.

25 Since the database used for image processes is separated, the need for re-compiling library modules that look up the database can be obviated.

Third to Fifth Embodiments (Figs. 19 to 30)

Upon controlling a printer to print by a printer driver, color conversion, color correction, and grayscale correction are done. For this purpose, the printer driver generates a corrected LUT from rank information of printer heads and stores it in correspondence with a head ID. In an actual print process, the printer driver reads the head ID, converts an image using an LUT corresponding to the read ID, and sends data to the printer.

Sixth Embodiment (Figs. 31 to 47)

Associated print parameters are stored as link information in correspondence with each other. Also, extraction conditions indicating the influences of a given parameter manipulated by the user on other parameters are separately stored. When a parameter value has been changed, a printer driver acquires link information which matches an extraction condition including that value, and sets setup items indicated by the link information in a selected state described in the link information.

Since a rewritable extraction condition is interposed between the item manipulated by the user and link information, the printer driver can flexibly cope with a change in link information.

Seventh Embodiment (Figs. 48 to 52)

A printer driver makes a margin information offering unit generate margins of a paper sheet in a print process. The margin information offering unit searches an index table using as parameters the ON/OFF states of continuous paper and perforated paper as a paper condition given from the driver to obtain a table ID that matches the condition. The margin information offering unit loads a data table which describes margins in units of paper sizes on the basis of that table ID, and searches this data table using the paper size as a parameter given from the driver to determine margins. Upon receiving the determined margins, the driver starts a print process.

The preferred embodiments of the present invention will be described in detail hereinafter with reference to the accompanying drawings.

[First Embodiment]

Fig. 1 is a block diagram showing the arrangement of an image processing apparatus as an embodiment of a data conversion apparatus according to the present invention. In the following description of this embodiment, the data conversion apparatus is implemented by a printer driver program which generates print data to be sent to a printer in a print process.

Referring to Fig. 1, an output apparatus 205 can comprise, e.g., a color printer, which forms a color

print on a print paper sheet using four color inks, i.e., yellow (Y), magenta (M), cyan (C), and black (K) inks.

Note that the color printer may output six or seven colors, but an explanation of this embodiment will be

5 given using four colors. Print data composed of Y, M, C, and K density data used in this output apparatus 205 are obtained by image processes executed by a control apparatus 201, and the image processes include color correction, color conversion, grayscale correction, 10 quantization, and the like (to be described below).

<Arrangement of Computer System>

Fig. 18 is a block diagram of a computer system used when the image processing system shown in Fig. 1 is implemented by a computer. Note that all the first to 15 seventh embodiments are applied to this computer system.

Referring to Fig. 18, a host computer 3000 serving as a control apparatus comprises a CPU 1 which processes a document including figures, images, characters, tables (including spreadsheets), and the like on the basis of a 20 document processing program stored in a program ROM of a ROM 3, and systematically controls devices connected to a system bus 4. A RAM 2 serves as a main memory, work area, and the like of the CPU 1. A keyboard controller (KBC) 5 controls inputs from a keyboard 9 and a pointing device (not shown). A CRT controller (CRTC) 6 controls 25 display on a CRT display 204. A disk controller (DKC) 7

00597403 062100
007290 0042660

controls access to an external memory 203 which includes a hard disk (HD), floppy disk (FD), and the like, and stores a boot program, various applications, font data, user files, edit files, and the like. A printer
5 controller (PRTC) 8 is connected to a printer 205 via a predetermined two-way interface (two-way I/F) 21 and executes a communication control process with the printer 205. Note that the CPU 1 executes a rasterization process of outline fonts onto a display
10 information RAM assured on, e.g., the RAM 2 to implement WYSIWYG (a function of matching the displayed contents with the print contents) on the CRT 204. Also, the CPU 1 opens various registered windows on the basis of commands instructed by a mouse cursor (not shown) or the
15 like, and executes various data processes. Furthermore, a printer driver (to be described later) is implemented when the CPU 1 executes a predetermined program.

In the printer 205, a printer CPU 12 systematically controls access to various devices
20 connected to a system bus 15 on the basis of a control program or the like stored in a program ROM of a ROM 13, and outputs an image signal as output information to a print unit (printer engine) 17 connected via a print I/F 16. The CPU 12 can communicate with the host computer
25 via a two-way I/F 21, and can send information or the like in the printer with the host computer. A RAM 19

00597403-062100
007290-004650

serves as a main memory, work area, and the like of the CPU 12. An input unit 18 controls exchange of status information such as print status information or the like with the host computer 3000 via the two-way I/F 21, and
5 can send information or the like in the printer to the host computer 3000. A memory controller (MC) 20 controls access to an external memory 14 which includes a hard disk (HD), floppy disk (FD), and the like, and stores a boot program, various applications, font data, user
10 files, edit files, and the like. A console 1012 includes a display panel and keyboard to offer information to the operator and allow the operator to input instructions.

<Arrangement of Software Module>

Fig. 17 is a block diagram showing software
15 modules that pertain to a print sequence executed by the control apparatus 201, i.e., the host computer 3000 shown in Fig. 18. Fig. 17 does not illustrate any modules that do not pertain to a print process. Also, Fig. 17 shows the software arrangement for all the first
20 to seventh embodiments.

Referring to Fig. 17, an application 1701, graphic engine 1702, printer driver 1703, and system spooler 1704 are program modules which reside as files saved in the external memory 203 shown in Fig. 18, and are loaded
25 onto the RAM 2 by an OS or a module that uses the corresponding module when they are executed.

data to the printer 204 via the system spooler 1704
which has been loaded onto the RAM 2 by the OS, and the
I/F 21.

The print data output from the printer driver is
5 temporarily input to the system spooler 1704, and is
then output to the printer 205.

<Arrangement of Ink-jet Printer>

Fig. 16 is a perspective view of an ink-jet
printer IJRA as an example of the output apparatus 205.
10 Note that the printer shown in Fig. 16 can be used as a
printer in all the first to seventh embodiments.

Referring to Fig. 16, a lead screw 5004 rotates
via driving force transmission gears 5011 and 5009 upon
forward/reverse rotation of a driving motor 5013. A
15 carriage HC, which engages with a spiral groove 5005 of
the lead screw 5004, has a pin (not shown), and
reciprocally moves in the directions of arrows a and b.
Y (yellow), M (magenta), C (cyan), and Bk (black)
ink-jet cartridges IJC are mounted on this carriage HC.
20 A paper pressing plate 5002 presses a paper sheet
against a platen 5000 along the moving direction of the
carriage HC. Photocouplers 5007 and 5008 confirm the
presence of a lever 5006 of the carriage in the
corresponding region, and detect a home position where,
25 e.g., the rotational direction of the motor 5013 is
switched. A member 5016 supports a cap member 5022 that

caps the front surface of each print head to attain suction recovery of print heads via an intra-cap opening 5023. A member 5019 holds a cleaning blade 5017 to be movable in the back-and-forth direction. These members
5 are supported by a main body support plate 5018. The blade 5017 is not limited to such specific one, but a known cleaning blade can be applied to this embodiment. A lever 5021 initiates suction of the suction recovery. The lever 5012 moves upon movement of a cam 5020 which
10 engages with the carriage, and its movement is controlled by a known transmission mechanism such as clutch switching by the driving force from a driving motor.

Referring to Fig. 1, the control apparatus 201 has
15 a CPU which executes data processes that pertain to this system such as an image process (to be described later), an initialization process therefor, and the like, and operation control of respective mechanical components. The storage device 203 includes general external storage
20 devices such as memories (ROM, RAM, or the like), a hard disk, a floppy disk, and the like, and stores a database including look-up tables which will be described later in an embodiment of the present invention, and a calculation segment.

25 For example, an image scanned by a scanner is stored in the storage device 203, and the operator of

002290-064560
this system can desirably edit the image displayed on a
display device 204 such as a CRT or the like by
operation inputs from an input device 202 including a
keyboard, mouse, and the like to obtain an image to be
5 printed out by the output apparatus 205.

The image obtained by this system in this manner
is expressed by grayscale data of luminance signals R, G,
and B, and undergoes an image process so as to be
converted into print data of the output apparatus 205.

10 Note that the scope of the present invention is
not limited to the aforementioned specific system. For
example, image processes (color correction, color
conversion, grayscale correction, and quantization) are
done in an apparatus such as a copying machine, as is
15 well known, and the present invention can also be
applied to such apparatus or system.

The color correction process in this case is that
from 8-bit R, G, and B data into 8-bit R', G', and B'
data. The color conversion process is that from 8-bit R',
20 G', and B' data into 8-bit C, M, Y, and K data. The
grayscale correction process is that from 8-bit C, M, Y,
and K data into 8-bit C', M', Y', and K' data. The
quantization process is that from 8-bit C', M', Y', and
K' data into 1-bit c, m, y, and k data. The color
25 correction, color conversion, grayscale correction, and
quantization at that time are implemented using look-up

tables (LUTs). These processes are executed by a printer control program, a so-called printer driver, which is prepared in units of printer models.

<Structure of Database File>

5 Figs. 2 and 3 show the concept of the present invention.

Referring to Fig. 2, a color correction/color conversion module 206 includes a search routine section (table ID search section) 212 for obtaining all table
10 IDs for print modes, and a color correction/color conversion processing section 213. Also, referring to Fig. 3, a grayscale correction/quantization module 208 includes a search routine section (table ID search section) 212 for obtaining all table IDs for print modes,
15 and a grayscale correction/quantization processing section 214. The "search routines for obtaining all table IDs for print modes" included in both the modules are identical functions. In Figs. 2 and 3, a database 207 is a database file including model-dependent
20 information of a printer, and Figs. 2 and 3 illustrate the same one. The database file 207 includes a search table LUT1 (209) including table IDs which correspond to print modes designated by user interface (UI) information and are required for various modules, and
25 actual tables LUT2 (210, 211) used by various modules.

Note that the UI information includes print conditions and the like input by the user.

05597403-062100

A table 215 shown in Fig. 4 is an example of the LUT1 (209) shown in Fig. 2, and consists of a plurality of tables LUT1 (tables including all table IDs corresponding to print modes). Referring to Fig. 4, the table 215 includes a print mode section 215a and table ID section 215b. The print mode section 215a lists combinations of the paper type (normal paper/OHP paper), quantization method (error diffusion/dithering), and print quality (best quality/middle quality) as keys. The table ID section 215b includes table IDs as identifiers of color correction tables, color conversion tables, grayscale correction tables, and dither matrix tables in correspondence with the print modes.

A table 216 shown in Fig. 5 is an example of the LUT2 (211) shown in Fig. 3, and includes a plurality of tables LUT2 (color correction table IDs, color conversion table IDs). A table 217 shown in Fig. 6 includes a plurality of tables LUT2 (grayscale correction table IDs, dither matrix table IDs). These tables 216 and 217 respectively include table ID sections 216a and 217a, and actual table sections 216b and 217b.

<Database Search>

In order to acquire an LUT used in image correction or conversion, the printer driver determines a print mode (e.g., paper type: normal paper, print quality: best quality, quantization: error diffusion) on the basis of setups included in the UI information, and passes that print mode to the color correction/color conversion module. The color correction/color conversion module searches for the passed print mode using the table ID search section 212 included therein, and loads a table LUT1 including the color correction table ID and color conversion table ID corresponding to the passed print mode from the database file 209. The color correction/color conversion module searches the table 210 for the color correction and color conversion table IDs included in the loaded table, and loads actual tables corresponding to these table IDs from the plurality of tables LUT2 (210) as those actually used thereby. The color correction/color conversion module then executes a normal color correction/color conversion process using the loaded tables LUT2.

Likewise, the grayscale correction/quantization module executes processes along the same flow. That is, the printer driver passes a print mode (e.g., paper type: normal paper, print quality: best quality, quantization: error diffusion) determined based on the setups included in the UI information to the grayscale

correction/quantization module. The grayscale correction/quantization module loads tables LUT1, which include the grayscale correction table ID and dither matrix table ID corresponding to the determined print mode, from the database file 209 using the table ID search section 212 included therein. The grayscale correction/quantization module searches the table 211 using the gradation correction and dither matrix table IDs included in the loaded tables, and loads tables LUT2 actually used thereby from the plurality of tables LUT2 (211). The grayscale correction/quantization module then executes a normal gradation correction/quantization process.

<Print Process Sequence>

Fig. 7 is a flow chart showing the print process sequence by the print system shown in Fig. 1. In Fig. 7, steps S701 to S703 are processes executed by the printer driver. When the user instructs a print process and inputs required information (e.g., paper type, print quality, quantization method) and the like, the process shown in Fig. 7 starts. Image data to be printed undergoes a color correction/color conversion process (step S701). The image data then undergoes grayscale correction/quantization (step S702), and is compressed or its data format is converted into a format that the printer can interpret, as needed (step S703). Upon

completion of these processes by the printer driver, the image data is sent to the printer shown in Fig. 16, and is printed (step S704).

Fig. 8 is a flow chart showing the processing sequence executed by the color correction/color conversion module 206, and this process corresponds to step S701 in Fig. 7. The table ID search section 212 searches the table 209 for a table ID using the print mode as a key (step S801). If the table ID is obtained, the color correction/color conversion module searches the tables (the plurality of tables LUT2) 210 using that table ID and loads a color correction table and color conversion table corresponding to the table ID onto a memory (step S802). The color correction/color conversion module executes color correction and color conversion using the loaded color correction and color conversion tables (step S803).

Fig. 9 is a flow chart showing the processing sequence executed by the grayscale correction/quantization module 208, and this process corresponds to step S702 in Fig. 7. The table ID search section 212 searches the table 209 for a table ID using the print mode as a key (step S901). If the table ID is obtained, the grayscale correction/quantization module searches the tables (the plurality of tables LUT2) 211 using that table ID and loads a grayscale correction

table and quantization table (dither matrix table)
corresponding to the table ID onto a memory (step S902).
The color correction/color conversion module executes
color correction and color conversion using the loaded
5 grayscale correction and quantization tables (step S903).

Fig. 10 is a flow chart showing the table ID
search process in step S801 in Fig. 8 and step S901 in
Fig. 9. A print mode is determined based on the input UI
information (step S1001), and LUT1 is searched using the
10 determined print mode to acquire all corresponding table
IDs (step S1002). This sequence is done by the table ID
search section 212.

In this manner, the look-up tables are held as a
database independently from the respective correction
15 and conversion modules, and are searched to obtain a
look-up table corresponding to the print mode, thus
executing correction and conversion.

<Maintenance of Look-up Table>

Fig. 11 shows an example wherein the contents of
20 the look-up table have been changed. Referring to
Fig. 11, a look-up table 2181 corresponding to table ID
"color correction table 01" in the table 218 has been
updated. For example, assume that tincture for a given
print mode is to be corrected upon revising the printer
25 driver. In this case, in the conventional printer driver,
since a color correction module and color conversion

module respectively hold color correction tables and color conversion tables, i.e., since those tables are looked up by only the module that uses the tables, these modules must be changed upon correcting tincture. By

5 contrast, according to the present invention, tincture can be corrected by changing the color correction table and color conversion table included in the database without changing the color correction module and color conversion module, as shown in Fig. 11.

10 Fig. 12 shows a database maintenance module 1201 and the database 207. Upon maintenance as well, in order to acquire a table to be maintained, the table ID search section 212 searches a table ID, and a look-up table is acquired based on the table ID. A table maintenance

15 module 1202 performs maintenance required for the acquired table, and writes back that table at an original position corresponding to the table ID.

Fig. 13 is a flow chart showing the table maintenance sequence. A table ID is searched in the sequence shown in Fig. 10 (step S1301), and a table LUT2

20 to be maintained, i.e., the entity of the table, is searched using the acquired table ID and is loaded (step S1302). The loaded table is updated by user's operations or by overwriting a separately prepared table thereon

25 (step S1303). Finally, the updated look-up table is

written back in the database as a table corresponding to that table ID (step S1304).

As described above, according to this embodiment, since the database file is divided into two groups LUT1 and LUT2, and the LUT1 includes table IDs for determining the LUT2, the LUT2 is indirectly accessed by each module which uses the table. In this manner, the color correction/color conversion module, and the grayscale correction/quantization module never directly access the LUT2 inside these modules.

For this reason, the address of an LUT looked up in the module can be prevented from being changed upon maintenance of the database, and maintenance of the database can be done independently of that of modules which use the database. Also, the need for changing the correction and conversion modules can be obviated upon maintenance of look-up tables, and labors required upon maintenance of the database such as change procedures, test procedures, and the like can be saved. Since the respective modules need not be changed, inconsistency (e.g., the LUT has been updated in a given module but not in another module) among modules can be prevented.

On the other hand, printer driver programs for controlling a plurality of models of printers may use a common image processing module, and other control modules and look-up tables that pertain to image

processes such as color correction, color conversion,
grayscale correction, quantization, and the like may be
provided in units of printer models. In this case, the
common image processing module is used, but look-up
5 tables corresponding to a given printer model are loaded.
In this manner, the time and cost required for
developing model-dependent image processing module
programs can be saved.

In this embodiment, table entries have been
10 explained as look-up tables used in image processes.
However, the present invention is not limited to the
image processes. For example, when data and tables
registered in a database are used from a given program,
the present invention can be applied using these data
15 and tables as entries of the database.

[Second Embodiment]

Fig. 14 is a schematic diagram showing an example
of the arrangement of a printer driver 200 according to
the second embodiment of the present invention.

20 A printer driver 200 generates print data on the
basis of image data acquired from an operating system
100, and sends it to a printer 500. The printer driver
200 is mainly comprised of a core module 300 which
exchanges data with the operating system 100 and printer
25 500, controls a user interface, and so forth, and
library modules prepared in units of functions such as

an image processing module 301, binary processing module 302, and the like. In case of the printer driver, the library modules are called by the core module 300. In this case, each library module receives information such as the type of print paper, print mode, and the like from the core module 300. Each library module searches a database 400 for a look-up table, output gamma table, and the like on the basis of various kinds of information received from the core module 300, and executes a process to obtain an appropriate print result.

Note that the database 400 combines look-up tables required for the image processing module 301, binary processing module 302, and the like, and has the same structure as the database in the first embodiment, which has been exemplified in Figs. 4 to 6.

The arrangement of a library module will be explained below taking the image processing module as an example.

Fig. 15 is a schematic diagram showing an example of the arrangement of the image processing module. The image processing module 301 comprises an image processing section 600, data storage section 601, and database search section 602. The image processing section 600 inputs various kinds of information of the printer received from the core module 300 to the database search section 602. The database search section

00597403 062400
602 performs the same process as that of the table ID search section in the first embodiment. That is, the database search section 602 searches the database 400 on the basis of the received information, and outputs a search result to the image processing section 600. As the search result, a table ID is obtained. The image processing section 600 reads look-up tables required for image processes from the database on the basis of the search result, and stores the read tables in the data storage section 601. After that, the image processing section 600 receives image data from the core module 300, executes image processes on the basis of the look-up table data stored in the data storage section 601, and outputs the image data that has undergone the image processes to the core module 300.

The database search section 602 is incorporated not only in the image processing module 301 but also in other library modules, and a single database can be searched from a plurality of library modules.

20 A case will be examined below wherein a plurality of printers 1 and 2 are connected to a personal computer or the like, and their driver programs are installed in the computer. When a printer driver for printer 1 is installed, modules such as the core module 300, image processing module 301, binary processing module 302, and the like, and the database 400 are installed.

When a printer driver for printer 2 is then installed, the modules such as the core module 300, image processing module 301, binary processing module 302, and the like are not installed since they are
5 common to those for printer 1, and processing modules required for printer 2 and a database 401 are installed.

When the user has selected a given printer, e.g., printer 1, upon instructing a print process during execution of an application program, the file name of
10 the database 400 corresponding to printer 1 is set in the database search sections 602 of the respective modules such as the image processing module, binary processing module, and the like, thus allowing access to the database corresponding to the selected printer.

15 Note that the search method of the database search section 602 is not particularly limited. Since the database 400 is independent from the library modules, when the contents of the database, i.e., look-up tables to be read by the image processing module 301 are to be
20 changed, the image processing module 301 need not be re-compiled, and the library modules and database can be efficiently developed.

In this manner, even when a change in database such as addition of new print paper, and the like
25 influences a plurality of library modules, the library modules influenced by that change need not be

re-compiled, and the contents of the database can be efficiently and easily changed.

Upon version-up of a driver program, the contents of the database can be efficiently and easily changed.

5 As described above, according to the printer drivers of the first and second embodiments, the look-up tables can be easily maintained independently from processes that use those tables, and consistency among modules which use the look-up tables can be prevented
10 from impairing.

Also, upon version-up of a driver program, the contents of the database can be efficiently and easily changed.

[Third Embodiment]

15 Fig. 19 is a block diagram showing the arrangement of an image processing apparatus to which the present invention can be applied.

An output apparatus 205 is a color printer, which forms a color print on a print paper sheet using four
20 color inks, e.g., yellow (Y), magenta (M), cyan (C), and black (K) inks. Note that the color printer may output six or seven colors, but an explanation of this embodiment will be given using four colors. Print data composed of Y, M, C, and K density data used in this
25 output apparatus 205 are obtained by image processes executed by a control apparatus 201, and the image

processes include color correction, color conversion, grayscale correction, quantization, and the like (to be described later). The output apparatus 205 includes a storage unit 205a for storing head information (to be described later).

The control apparatus 201 has a CPU which executes data processes that pertain to this system such as an image process (to be described later), an initialization process therefor, and the like, and operation control of respective mechanical components. A storage device 203 includes general external storage devices such as memories (ROM, RAM, or the like), a hard disk, a floppy disk, and the like, and stores a database including look-up tables which will be described later in an embodiment of the present invention, and a calculation segment. Also, the storage device stores image data of a standard pattern for calibration, and program codes that implement the sequences of the flow charts to be described later. These data and programs may be supplied to this image processing system via a medium such as a removable optical disk, floppy disk, or the like.

With this arrangement, for example, an image scanned by a scanner is stored in the storage device 203, and the operator of this system can desirably edit the image displayed on a display device 204 such as a CRT or the like by operation inputs from an input device 202

including a keyboard, mouse, and the like to obtain an image to be printed out by the output apparatus 205. The input device 202 may include an image scanner. When the image scanner is equipped, a standard pattern output for calibration can be scanned by that scanner. In this case, the I/O characteristics of the image scanner must be corrected to obtain linear I/O characteristics, and LUTs and the like required for the correction are prepared.

The image obtained by this system in this manner is expressed by grayscale data of luminance signals R, G, and B, and undergoes color correction, color conversion, grayscale correction, and quantization so as to be converted into print data of the output apparatus 205.

Note that the scope of the present invention is not limited to the aforementioned specific system. For example, image processes (color correction, color conversion, grayscale correction, and quantization) are done in an apparatus such as a copying machine, as is well known, and the present invention can also be applied to such apparatus or system.

Various correction processes executed by the control apparatus 201 will be briefly explained below. The color correction process is that from 8-bit R, G, and B data into 8-bit R', G', and B' data. The color conversion process is that from 8-bit R', G', and B' data into 8-bit C, M, Y, and K data. The grayscale

correction process is that from 8-bit C, M, Y, and K data into 8-bit C', M', Y', and K' data. The quantization process is that from 8-bit C', M', Y', and K' data into 1-bit c, m, y, and k data. The color correction, color conversion, grayscale correction, and quantization at that time are implemented using look-up tables (to be also referred to as LUTs hereinafter).

Fig. 16 is a perspective view of the mechanism of an ink-jet printer as an example of the output apparatus 205. Referring to Fig. 16, a lead screw 5004 rotates via driving force transmission gears 5011 and 5009 upon forward/reverse rotation of a driving motor 5013. A carriage HC, which engages with a spiral groove 5005 of the lead screw 5004, has a pin (not shown), and reciprocally moves in the directions of arrows a and b. Y (yellow), M (magenta), C (cyan), and Bk (black) ink-jet cartridges IJC are mounted on this carriage HC. A paper pressing plate 5002 presses a paper sheet against a platen 5000 along the moving direction of the carriage HC. Photocouplers 5007 and 5008 confirm the presence of a lever 5006 of the carriage in the corresponding region, and detect a home position where, e.g., the rotational direction of the motor 5013 is switched. A member 5016 supports a cap member 5022 that caps the front surface of each print head to attain suction recovery of print heads via an intra-cap opening

5023. A member 5019 holds a cleaning blade 5017 to be movable in the back-and-forth direction. These members are supported by a main body support plate 5018. The blade 5017 is not limited to such specific one, but a known cleaning blade can be applied to this embodiment. A lever 5021 initiates suction of the suction recovery. The lever 5021 moves upon movement of a cam 5020 which engages with the carriage, and its movement is controlled by a known transmission mechanism such as clutch switching by the driving force from a driving motor.

Note that each ink-jet cartridge IJC comprises a memory (not shown), which stores a head ID as a unique identifier of each cartridge, and head rank information indicating the state of the head in the manufacture, e.g., an ink ejection state or the like. Such information (head information) is read out and used in a print process or calibration.

Fig. 20 is a schematic diagram of software modules that pertain to a print process in the image processing system of this embodiment.

Referring to Fig. 20, a printer driver module 2006 converts image data which was generated by an application program or the like and has a format according to an operating system or the like into data of a format the output apparatus 205 can print. The data

(print data) generated by the driver module 2006 is sent to the output apparatus 205, and is printed out.

The driver module 2006 calls a calibration module 2008 and generates a new, corrected database file 2012 including a LUT corrected in a sequence to be described later, on the basis of an original database file 2011, which is prepared in advance and includes standard LUTs. Calibration may be launched by the user from a driver utility program or upon issuing a print start command, installing a driver, or exchanging a head.

Note that the original database file 2011 is a printer database 2020, as shown in Fig. 22, which includes commands as model information of the output apparatus 205, margin information, LUTs (interpolation tables) required for color correction/color conversion, LUTs (grayscale correction tables) required for grayscale correction, dither matrices required for quantization, and the like.

The generated database is looked up by a color correction/color conversion module 2009 or grayscale correction/quantization module 2010 upon executing a print process. In this case, the database used is selected in accordance with the ID of a head mounted on the output apparatus by looking up a file name management file 2013, which stores head IDs and database

file names in correspondence with each other, by a file name acquisition module 2007.

<Calibration Sequence>

5 In calibration, a database file is generated in correspondence with the individual differences, aging, and the like of the printer and ink head. For example, the printer driver fetches the head ID and head rank information (e.g., C: +2, M: 0, Y: -1, K: +1) from the printer main body, and sends that information to the
10 calibration module, thus generating a database file including an LUT (for example, a grayscale correction table 2023 in Fig. 23) that matches the head rank. Alternatively, the user may conduct a test print to determine a head rank based on the test print result,
15 and calibration may be done based on that head rank. Alternatively, density information at each gray level may be measured from a test print result of a standard pattern, which is prepared in advance, using an external device, the measurement result may be input to this
20 image processing system via a removable storage medium or communication, and each LUT may be corrected based on that measurement result.

Figs. 25 and 26 respectively show the calibration processing sequences in the driver module and
25 calibration module. In this case, calibration is done by the last method mentioned above.

Referring to Fig. 25, when a calibration process of the driver module is launched, a standard pattern for calibration is output using the original database (step S2501). After that, the driver module waits until the measurement result of that output image is input (step S2502). In this case, the control waits for the input via a loop. Alternatively, the control may temporarily quit the process, and may restart it in response to the input.

Upon receiving image data as the measurement result of the standard pattern, the driver module reads out head information including the head ID and rank information from the output apparatus, and launches the calibration module (step S2503). The head information may be read out beforehand upon, e.g., starting up the system.

Fig. 26 shows the processing sequence of the calibration module launched in step S2503. The calibration module defines new rank information based on the image data received from the driver module (step S2601). After the rank information is defined, the calibration module changes an LUT in accordance with the value of that rank information (step S2602).

The rank information indicates, e.g., an ink ejection state of the head in units of colors. A value "0" is a standard value, and the ink ejection amount

decreases when the value increases in the positive direction; the ink ejection amount increases when the value increases in the negative direction. For this reason, as rank information for a given color assumes a larger value, grayscale correction corrects to increase the grayscale value of that color. Therefore, a grayscale correction LUT is corrected in accordance with the rank information, as shown in Fig. 23.

Finally, a database file including the generated LUT is stored as the corrected database file 2012 in Fig. 20. In this case, a file name management file 2013 used to manage the name of the new database file is generated, as shown in Fig. 24. The file name management file 2013 includes head IDs 2021 and corresponding database file names 2022. Therefore, when a new head is mounted, its ID must be registered in the file name management file 2013.

When calibration is done based on the head rank determined by the user, since the input information is rank information, the control section need not determine rank information. For this reason, the driver module need only execute step S2503 in Fig. 25, and the calibration module need only execute steps S2602 and S2603 in Fig. 26.

Fig. 27 shows the processing sequence of the driver module 2006 upon executing a print process.

driver module. Alternatively, the processing sequence at that time may be executed without the intervention of the driver. In this case, if the file name acquisition module determines that there is no file name

5 corresponding to the head ID, it launches the calibration module to generate a database according to the head rank information, register it as a corrected database file, and register its database file name in the file name management file 2013 in correspondence

10 with the head ID. Upon completion of registration, the module 2007 returns the file name of the new database file to the driver module 2006. In this manner, the driver module can acquire and use the database file name corresponding to the head ID independently of whether or

15 not the head ID is registered. Therefore, in the processing contents shown in Fig. 27, the process in step S2704 need only be done after step S2701.

On the other hand, when an option that can use the original database file without calibration is prepared

20 by providing a switch for selecting whether or not calibration is done to a driver utility or the like, a print process without calibration may be done.

With the aforementioned arrangement and sequence, the head rank is updated in accordance with the

25 individual differences, aging, and the like of the printer main body and ink head, and a database file

including a look-up table corresponding to the updated head rank can be created, edited, and registered. In this manner, an optimal print result can always be obtained in correspondence with the head used. For example, even when a certain head forms a magenta-rich image if the original database file is used, a database file that has been calibrated in correspondence with that head is registered and used, thus maintaining color balance.

10 Since the database files are registered in units of heads, even when a plurality of printers are used or when a single printer is used while exchanging its head by various heads such as a monochrome head, four-color head, seven-color head, and the like, a
15 correction/conversion process optimal to each head is done, and a high-quality image can be output.

 Note that this embodiment has been explained using the ink-jet printer. However, the present invention can be applied to other printers. In this case, if a printer
20 uses an exchangeable print head, characteristic information corresponding to a head rank is held in correspondence with each head ID, and an LUT is corrected in correspondence with the held information. On the other hand, if a printer does not have any "head"
25 like in an electrophotographic printer, an identifier and characteristics unique to an exchangeable component

Then, the printer driver module 2014 calls a file name acquisition module 2015 to acquire a database file name corresponding to a model ID. The driver module calls a color correction/color conversion module and grayscale correction/quantization module using that database file name and executes a process, thus obtaining an optimal print result using the LUT corresponding to the head which is currently mounted.

With the aforementioned arrangement, the head rank is updated in accordance with individual differences, aging, and the like of the printer main body and ink head, and a database file including a look-up table corresponding to the updated head rank can be created and edited. In this manner, an optimal print result can always be obtained in correspondence with the head used.

Since the stored database corresponds to only one head, the storage capacity for that database can be saved.

[Fifth Embodiment]

Fig. 28 is a schematic diagram of software modules that pertain to a print process in the image processing system of this embodiment. Fig. 28 shows a case wherein a printer is designated as a print destination port. Since blocks in Fig. 28 having common reference numerals to those in Fig. 20 have the same functions as those in Fig. 20, a detailed description thereof will be omitted.

In the image processing system of this embodiment, the user can designate a print destination port via a user interface provided by, e.g., a printer driver module 2006. The user can designate, as a print
5 destination port, a local printer, a network printer, or a file on a communication line or a hard disk, which can be used by the image processing system of this embodiment. If the user designates a printer, a print process is done by the designated printer; if the user
10 designates a file, a print file generated by the driver module 2006 is stored in, e.g., a hard disk of the apparatus.

The printer driver module main body 2006 calls a calibration module 2008 and generates a new database
15 file 2012 on the basis of an original database file 2011. Calibration may be launched by a driver utility program or upon issuing a print start command, installing a driver, or exchanging a head. On the other hand, the calibration sequence may be the same as that shown in
20 Figs. 25 and 26 of the first embodiment. That is, the printer driver fetches the head ID and head rank information from the printer main body, and sends that information to the calibration module, thus generating an LUT which matches the head rank. Alternatively, as
25 described in the third embodiment, the user may conduct a test print to determine a head rank based on the test

print result, and calibration may be done based on that head rank input by the user.

As a result, the corrected database file 2012 stores LUT files according to the characteristics of the individual heads such as ink ejection states of the heads indicated by the rank information in correspondence with the head IDs. Upon generation of the corrected database file, a database name management file 2013 for managing its file name is also generated, as shown in Fig. 24. Such process is the same as the third embodiment.

Upon executing a print process, when a printer is designated as the print destination port, the printer driver module 2006 calls an original file name acquisition module 2015 that returns the original database file name to acquire the original database file name. If a corrected database file corresponding to the head ID of the head used has been generated, the driver module calls a corrected file name acquisition module 2014 which acquires a corrected database file name corresponding to the head ID. Then, the driver module calls a color correction/color conversion module and grayscale correction/quantization module using that database file name to execute a process, thus obtaining an optimal print result using the LUT corresponding to the head which is currently mounted.

When the printer driver 2006 fails to acquire the head ID, when a corrected database file is not normally generated, or when the database file name management file 2013 is not normally generated, it uses the
5 original database file using the initially acquired original database file name.

On the other hand, when a file is designated as the print destination port upon executing a print process, the printer driver uses the original database
10 file, as shown in Fig. 29. In this case, the driver module 2006 need not obtain printer-dependent information to output print data to a file. For this reason, the driver module 2006 uses the original
15 database file. This is because the characteristics of a head which may output print data (print file) output to a file cannot be specified. That is, even when the printer driver 2006 designates a specific printer and generates a print file in correspondence with the characteristics of that printer, since that print file
20 is not always printed using the head having characteristics used upon generating the print file, the driver module generates print data using the versatile original database file.

In this case, the printer driver module 2006 calls
25 the module 2015 that returns the original database file name. The driver module calls the color correction/color

conversion module and grayscale correction/quantization module using the obtained original database file name to execute a process.

Fig. 30 shows the sequence upon executing a print process in this embodiment mentioned above.

The printer driver module 2006 acquires the original database file name via the original file name acquisition module 2015 (S3001). The driver module determines a print destination port (S3002). If the port is a file, the driver module executes an image process in accordance with an LUT in the original database file acquired in step S3001 (S3010).

On the other hand, if the print destination port is a printer, the driver module acquires the head ID of the printer (S3003). It is checked if head ID acquisition has succeeded (step S3004). If acquisition has failed, the driver module executes an image process in accordance with an LUT in the original database file (S3010). If head ID acquisition has succeeded, the driver module acquires a corrected database file name corresponding to the acquired head ID via the corrected file name acquisition module 2014 (S3005).

It is then checked if the corrected database file name corresponding to the head ID is obtained (step S3006). If no such file name is obtained, i.e., if no database file corresponding to the head ID is registered,

the driver module executes calibration, and registers a corrected database file name in the database management file (step S3007).

It is checked if the corrected database file is normally generated (step S3008). If the corrected database file is not normally generated, the driver module executes an image process using an LUT of the original database file (step S3010). If the corrected database file is normally generated, the driver module executes an image process using an LUT of the corrected database file (step S3009).

On the other hand, if it is determined in step S3006 that the corrected database file 2012 corresponding to the head ID has already been registered, the driver module executes an image process using an LUT of the corrected database file without calibration (step S3009).

If it is determined in step S3006 that the database file name management file 2013 is not normally generated, and a corrected database file which is to be used actually cannot be obtained, or if the corrected database file is not normally generated, the driver module executes an image process using an LUT of the original database file (step S3010).

In this way, in the image processing system of this embodiment, when the designated print destination

port is an apparatus having individual characteristics such as a printer or the like, and a unique LUT is required to correct its characteristics, the LUT corresponding to the characteristics is generated, and image data undergoes color correction, grayscale correction, and the like using the LUT to generate print data. For this reason, since the database file including a look-up table is generated and edited in correspondence with individual differences, aging, and the like of the printer main body and ink head, an optimal print result can always be obtained. For example, even when a magenta-rich head is used, formation of an image which is entirely tinged with red or gray balance holding errors can be eliminated.

15 On the other hand, if the designated print
destination port is a file or the like, and the final
output destination is unknown, print data is generated
using a standard LUT.

In this manner, when the characteristics of a printer that prints are known, optimal print data to such characteristics can be generated; if the characteristics are unknown, standard print data can be generated.

As described above, according to the printer
25 drivers of the third to fifth embodiments, since a
database file including a look-up table is generated in

accordance with individual differences, aging, and the like of characteristics of the output apparatus, a satisfactory print result can always be obtained. When the characteristics of the output apparatus are unknown, the output image quality can be maintained using a versatile database file.

[Sixth Embodiment]

A link information search apparatus and a method executed in that search apparatus according to an embodiment of the present invention will be described below with reference to the accompanying drawings. This link information search apparatus is used to appropriately maintain a combination of setup values for a print process, which is input via a user interface. The user interface is implemented by, e.g., the printer driver 1703 shown in Fig. 17 via the OS. Therefore, this link information search apparatus may be included in functions executed by the printer driver when the user makes print setups, in place of a standalone use.

<Arrangement of Link Information Search Apparatus>

Fig. 31 best illustrates characteristic feature of a link information search apparatus according to this embodiment, and the link information search apparatus will be explained below using Fig. 31.

Note that "link information" is parameter information which is given to an image processing

apparatus (e.g., a printer, facsimile apparatus, or the like) in close relation to a set or changed print condition. A desired print condition can be achieved by a combination of one or a plurality of pieces of
5 parameter information (link information).

A data processing unit 3101 executes various data processes to be described later. A display device 3102 displays the state of a printer driver to the user. A data input unit 3103 is used to input data when the user
10 changes setups of the printer driver or instructs to execute a print process. A changed value storage unit 3104 receives and stores a changed setup item and its setup value sent from the data processing unit 3101, when the user has changed the setups of the printer
15 driver via the data input unit 3103.

Upon extracting link information, the setup item and setup value which are stored in the changed value storage unit 3104 and have been changed by the user are sent to the data processing unit 3101. Reference numeral
20 3105 denotes a current value storage unit which stores the remaining setup items and all setup values after the changed setup item and setup value are stored in the changed value storage unit 3104.

As in the changed value storage unit 3104, upon
25 extracting link information, the setup items and setup values stored in the current value storage unit 3105 are

sent to the data processing unit 3101. A reference information determination unit 3106 receives a setup item that has been changed by the user from the data processing unit 3101, and determines a storage section to be referred to of a link information storage unit 3108 upon extracting link information on the basis of the received information.

An extraction condition setting unit 3107 pre-stores a condition required upon extracting link information. The link information storage unit 3108 includes a plurality of link information storage sections, and stores an information group to be changed to link with setup items of the printer driver, which have been changed by the user. A setup value information replace unit 3109 receives a link information group, which is obtained as a result of extraction of link information and is sent from the link information storage unit 3108 to the data processing unit 3101, and replaces the contents of the setup values of setup items, which are stored in the current value storage unit 3105 and are not changed, by the newly received link information. An extracted information storage unit 3110 stores link information as a result of extraction of link information.

<Link Information Change Process Sequence>

005597403-032100

The contents of this embodiment will be described in detail below. Fig. 38 is a flow chart for explaining the overall flow of the link information change process, and Fig. 39 is a flow chart for explaining details of link information acquisition.

Fig. 32 shows the printer driver setup window displayed on the screen by the display device 3102. In Fig. 32, the user can select setup items "ink cartridge", "paper type", "paper source", "grayscale print", "print quality", "dithering", "image data correction", and "photo data correction" of the functions of the printer in correspondence with his or her print purpose.

When the user wants to change the setup value of setup image "ink cartridge" of those of the printer driver from "black/color" to "black/photo" in Fig. 32, he or she selects a setup value "black/photo" of "ink cartridge" using an input device such as a keyboard, mouse or the like (step S3800 in Fig. 38). In response to this change, the data input unit 3103 informs the data processing unit 3101 that the changed setup item is "ink cartridge", and the setup value after the change is "black/photo" (step S3810).

Fig. 33 shows an example of the changed item and setup value information as objects to be changed, which are received by the data processing unit 3101. Upon receiving such information, the data processing unit

3101 sends the changed setup item and setup value after
the change to the changed value storage unit 3104, which
stores them (step S3820 in Fig. 38). Subsequently, the
data processing unit 3101 inspects the current setup
5 values of all setup items, and sends the inspection
result to the current value storage unit 3105, which
stores the received result (step S3830 in Fig. 38).

Fig. 34 shows an example of data stored in the
current value storage unit 3105. In this case, the
10 current value storage unit stores data indicating that
the setup value of "paper type" is "normal paper", that
of "paper source" is "auto sheet feeder", that of
"grayscale print" is "OFF", "print quality" is "second
(from left)", "dithering" is "pattern (high speed)",
15 "image data correction" is "OFF", and "photo data
correction" is "OFF".

Subsequently, the data processing unit 3101
informs the reference information determination unit
3106 of the changed setup item (step S3840 in Fig. 38).
20 Upon receiving this information, the reference
information determination unit 3106 determines link
information to be referred to in accordance with the
changed setup item, and informs the data processing unit
3101 of the ID of the link information storage section
25 in the link information storage unit 3108 to be referred
to (step S3850 in Fig. 38).

As the ID of the link information storage section to be referred to in the link information storage unit 3108, a plurality of link information storage sections must sometimes be referred to depending on the setup item that has been changed by the user, or no link information storage section must be referred to if the changed setup item does not influence other items at all (step S3860 in Fig. 38).

Fig. 37 shows an example of data stored in the reference information determination unit 3106. When the changed setup item is "ink cartridge", the ID numbers of link information storage sections to be referred to in the link information storage unit 3108 are 1, 2, 3, 4, 5, and 6. The storage sections with these IDs are referred to upon changing data. Likewise, when the changed setup item is "print quality", the IDs of link information storage sections to be referred to in the link information storage unit 3108 are 5 and 6.

Furthermore, when the changed setup item is "image data correction", since no ID of link information storage section to be referred to is described, there is no link information to be referred to. In this manner, depending on the setup item that has been changed by the user, a plurality of link information storage sections of the link information storage unit 3108 must be referred to, or some setup item does not sometimes

influence other items. When the item changed by the user is "ink cartridge", the ID numbers = 1, 2, 3, 4, 5, and 6 are returned to the data processing unit 3101 in step S3850.

5 Fig. 35 shows the relationship between the link information storage sections with the ID numbers = 1 to 6 in the link information storage unit 3108, which must be referred to when the user has changed the setup item "ink cartridge", and the corresponding contents.

10 The data processing unit 3101 sends the smallest one of the IDs received from the reference information determination unit 3106 to the extraction condition setting unit 3107. Upon receiving the ID, the extraction condition setting unit 3107 returns a condition of the
15 setup item required for acquiring link information to the data processing unit 3101 (step S3860 in Fig. 38).

 The data processing unit 3101 acquires a setup item and its setup value according to the extraction condition returned from the extraction condition setting
20 unit 3107 from the changed value storage unit 3104 and current value storage unit 3105, and accesses the link information storage unit 3108 to acquire information that matches the extraction condition (step S3870 in Fig. 38).

25 Fig. 36 shows an example of extraction conditions set in units of IDs. As can be seen from Fig. 36, for

example, the contents of the setup values of two setup items "ink cartridge" and "paper type" are required upon extracting data from link information storage section 1 (reference medium correction table), and setup item "ink
5 cartridge" is required upon accessing link information storage section 3 (grayscale correspondence table). The reference information determination unit 3106 determines appropriate ID numbers to be referred to on the basis of the relationship between the link information storage
10 sections and extraction conditions shown in Fig. 36. Link information is acquired in ascending order of IDs.

The data processing unit 3101 accesses the link information storage unit 3108 on the basis of the ID numbers to be referred to, which are determined by and
15 sent from the reference information determination unit 3106, thus acquiring required link information. This process will be described in detail below with reference to Fig. 39. Note that steps S3900 to S3920 in Fig. 39 overlap steps S3850 and S3860 in Fig. 38.

20 <Acquisition of Link Information>

The data processing unit 3101 receives the IDs of link information storage sections to be referred to from the reference information determination unit 3106 (step S3900 in Fig. 39), and then informs the extraction
25 condition setting unit 3107 of the received IDs (step S3910 in Fig. 39). The extraction condition setting unit

2107 informs the data processing unit 3101 of conditions required for extraction, which are different in units of IDs (step S3920 in Fig. 39).

09597403-062100

The data processing unit 3101 receives the

5 conditions required for extraction from the extraction condition setting unit, sets the required setup items and setup values from the changed value storage unit 3104 and current value storage unit 3105, accesses one that matches the ID of the plurality of link information

10 storage sections of the link information storage unit 3108 that stores information which matches the data condition, and acquires link data which matches the extraction condition (step S3930 in Fig. 39). This acquisition process repeats itself in correspondence

15 with the number of IDs sent from the reference information determination unit 3106.

For example, as shown in Fig. 37, when "ink cartridge" has been changed, link information is referred to from all link information storage sections

20 with IDs = 1, 2, 3, 4, 5, and 6 in the link information storage unit 3108 to progress the extraction process.

Fig. 40 shows the contents of link information storage section 1 (reference medium correction table) which corresponds to the ID = 1. As can be seen from

25 Fig. 40, a combination of "ink cartridge" and "paper type" is an extraction condition. Fig. 40 exemplifies

link information storage section 1, but the same applies to other link information storage sections.

In order to refer to link information storage section 1 (reference medium correction table) from the extraction condition setting unit 3107, "ink cartridge" and "paper type" are required (Fig. 36), the current values or changed data are set as the contents of these setup items on the basis of the charged value storage unit 3104 and current value storage unit 3105, and link information storage section 1 (reference medium correction table) with the smallest ID number is accessed to search for link information under the extraction condition "ink cartridge" = "black/photo" and "paper type" = "normal paper". Information that matches the condition (in this case, link information which changes "paper type" to "coated paper") can be obtained. This result is immediately sent to the data processing unit 3101.

In this manner, the information that matches the extraction condition is sent from the link information storage unit 3108 to the data processing unit 3101, which sends the received link information to the extracted information storage unit 3110. Upon receiving this information, the extracted information storage unit 3110 stores the link information (step S3940 in Fig. 39).

Furthermore, upon receiving the link information, the data processing unit 3101 sends this information to the setup value information replace unit 3109, which replaces the setup value of the setup item included in
5 the received data (in this case, setup value "coated paper" of setup item "paper type") by setup value "normal paper" of the setup item stored in the current value storage unit 3105 (step S3950 in Fig. 39).

The link information extraction process ends here.
10 When the condition "ink cartridge" has been changed, link information storage sections with ID numbers = 1 to 6 are accessed in turn in ascending order of IDs to obtain the extraction condition after the change again. The subsequent processes (acquisition of link
15 information for the ID number = 2 and the subsequent ID numbers) will be explained below.

<Link Information Acquisition Example 1>

Link information storage section 2 (medium correspondence table) shown in Fig. 41, which
20 corresponds to the ID number = 2, is accessed to acquire link information.

In order to obtain link information from link information storage section 2 (medium correspondence table), since it is determined based on information from
25 the extraction condition setting unit 3107 that "ink cartridge" and "paper type" are required, the contents

of the setup values of these setup items are set based on the changed value storage unit 3104 and current value storage unit 3105 to access link information storage section 2 (medium correspondence table). At this time, since the setup value information replace unit 3109 has already replaced the contents of "paper type" from "normal paper" to "coated paper", the contents of the two setup items to be set in this case are "black/photo" for "ink cartridge", and "coated paper" for "paper type".

Four pieces of information in link information storage section 2 (medium correspondence table) that match this condition instruct to "delete" "paper type" = "normal paper", to "select" "paper type" = "coated paper", to "delete" "paper type" = "OHP", and to allow "paper type" = "gloss paper" "selectable". The four pieces of information that match the condition are sent to the data processing unit 3101, which sends the received link information to the extracted information storage unit 3110. Upon receiving such information, the extracted information storage unit 3110 stores the link information.

The data processing unit 3101 also sends the returned link information to the setup value information replace unit 3109, which replaces data which is instructed to "select", i.e., data of "coated paper", of the setup values of the setup items included in the

received data. In this case, since "normal paper" has already been deleted, and "coated paper" has been selected, the setup values remain the same apparently.

<Link Information Acquisition Example 2>

5 Link information storage section 3 (grayscale correspondence table) shown in Fig. 42, which corresponds to the ID = 3, is accessed to acquire link information.

10 In order to obtain link information from link information storage section 3 (grayscale correspondence table), since it is determined based on information of the extraction condition setting unit 3107 that "ink cartridge" is required, the contents of the setup value of this setup item are set based on the changed value

15 storage unit 3104 to access link information storage section 3 (grayscale correspondence table). Since the contents of extraction condition "ink cartridge" are "black/photo", two pieces of link information that match this condition instruct to allow "grayscale" = "ON"

20 "selectable" and to "select" "grayscale" = "OFF". The two pieces of information that match the condition are sent to the data processing unit 3101, which sends the received link information to the extracted information storage unit 3110. Upon receiving this information, the

25 extracted information storage unit 3110 stores the link information.

The data processing unit 3101 also sends the returned link information to the setup value information replace unit 3109, which replaces the current setup value by the setup value of the setup item included in the received data. In this case, since "grayscale" = "OFF" which is instructed to "select" has already been selected, no replacement is done apparently.

<Link Information Acquisition Example 3>

Link information storage section 4 (quality-level correspondence table) shown in Fig. 43, which corresponds to the ID number = 4, is accessed to acquire link information. In order to obtain link information from link information storage section 4 (quality-level correspondence table), since it is determined based on information from the extraction condition setting unit 3107 that "ink cartridge" and "paper type" are required (Fig. 36), the contents of the setup values of these setup items are set based on the changed value storage unit 3104 and current value storage unit 3105 to access link information storage section 4 (quality-level correspondence table). Five pieces of information that match the condition "ink cartridge" = "black/photo" and "paper type" = "coated paper" describe to allow "print quality" = "fifth level" "selectable", to "select" "print quality" = "fourth level", and to "delete" "print quality" = "first level" to "third level". This means

that when "ink cartridge" is "black/photo", and "coated paper" is selected, the first to third levels of the print quality are deleted (unselectable), the fourth level is selected, and the fifth level is selectable.

5 The five pieces of "print quality" information that match the condition are sent to the data processing unit 3101, which sends the received link information to the extracted information storage unit 3110. Upon receiving such information, the extracted information
10 storage unit 3110 stores the link information. Upon receiving the link information, the data processing unit 3101 sends the received information to the setup value information replace unit 3109, which replaces the
15 current setup value by the setup value of the setup item included in the received data, i.e., setup value "second level" stored in the current value storage unit 3105 by setup value "fourth level" of setup item "print quality".
<Link Information Acquisition Example 4>

 Link information storage section 5 (quality
20 message-binarization method correspondence table) shown in Fig. 44, which corresponds to the ID number = 5, is accessed to acquire link information. In order to obtain link information from link information storage section 5
(quality message-binarization method correspondence
25 table), since it is determined based on information from the extraction condition setting unit 3107 that "ink

cartridge", "paper type", and "print quality" are required, the contents of the setup values of these setup items are set based on the changed value storage unit 3104 and current value storage unit 3105 to access link information storage section 5 (quality message-binarization method correspondence table).

At this time, since the setup value information replace unit 3109 has already replaced "paper type" from "normal paper" to "coated paper", and "print quality" to "fourth level", the contents of the setup values of these setup items are "black/photo" for "ink cartridge", "coated paper" for "paper type", and "fourth level" for "print quality".

Upon searching link information storage section 5 (quality message-binarization method correspondence table) under such condition, four pieces of found information describe to "select" "quality message" = "PHOTO", to "delete" "dithering" = "pattern (high speed)" and "pattern", and to "select" "dithering" = "error diffusion". This means to display print quality message (print mode in Fig. 32) "PHOTO", to select "error diffusion" of dithering processes, and to delete other processes. The four pieces of information are sent to the data processing unit 3101, which sends the received link information to the extracted information storage unit 3110. Upon receiving these information, the

extracted information storage unit 3110 stores the link information.

Upon receiving the link information, the data processing unit 3101 sends the received information to the setup value information replace unit 3109, which replaces the current setup value by the setup value of the setup item included in the received data, i.e., setup value "pattern (high speed)" stored in the current value storage unit 3105 by setup value "error diffusion" of setup item "dithering".

<Link Information Acquisition Example 5>

Link information storage section 6 (resolution correspondence table) shown in Fig. 45, which corresponds to the ID = 6, is accessed to acquire link information.

In order to obtain link information from link information storage section 6 (resolution correspondence table), it is determined based on information from the extraction condition setting unit 3107 that "ink cartridge", "paper type", "print quality", "dithering", and "grayscale" are required (Fig. 36). The contents of the setup values of these setup items are set based on the changed value storage unit 3104 and current value storage unit 3105 to access link information storage section 6 (resolution correspondence table).

At this time, since the setup value information
replace unit 3109 has already replaced "paper type" from
"normal paper" to "coated paper", "print quality" to
"fourth level", and "dithering" from "pattern (high
5 speed)" to "error diffusion", the contents of the setup
values of these setup items are "black/photo" for "ink
cartridge", "coated paper" for "paper type", "fourth
level" for "print quality", "error diffusion" for
"dithering", and "OFF" for "grayscale".

10 Upon searching link information storage section 6
(resolution correspondence table) under such condition,
three pieces of found information describe to "select"
"vertical resolution" = "720", to "select" "horizontal
resolution" = "720" and "pattern", and to "select"
15 "smoothing information" = "smoothing". The three pieces
of information are sent to the data processing unit 3101,
which sends the received link information to the
extracted information storage unit 3110. Upon receiving
these information, the extracted information storage
20 unit 3110 stores the link information. In this manner, a
series of link information acquisition processes come to
an end.

Fig. 46 shows link information stored in the
extracted information storage unit 3110. That is, these
25 pieces of link information instruct to select "paper
type" = "coated paper", to delete "paper type" = "normal

paper" and "OHP", to allow "grayscale" = "ON" selectable,
to select "grayscale" = "OFF", to allow "print quality"
= "fifth level" selectable, to select "print quality" =
"fourth level", to delete "print quality" = "first
5 level" to "third level", to select "quality message" =
"PHOTO", to select "dithering" = "error diffusion", to
delete "dithering" = "pattern (high speed)" and
"pattern", to select "vertical and horizontal
resolutions" = "720", and to select "smoothing
10 information" = "smoothing".

The extracted information storage unit 3110 sends
these pieces of link information to the data processing
unit 3101, which displays this result on the display
device 3102 (step S3880 in Fig. 38).

15 Fig. 47 shows the printer driver window displayed
after "ink cartridge" has been changed from
"black/color" to "black/photo" via a series of processes
mentioned above.

In Fig. 47, "ink cartridge" is changed to
20 "black/photo", "print quality" to "fourth level"
(instruct the fourth setup value from the left end), and
"dithering" to "error diffusion". The first, second, and
third levels of "print quality" are unselectable in
correspondence with "delete" choice, and the fifth level
25 is selectable. Also, "pattern" and "pattern (high
speed)" of "dithering" are unselectable.

As described in this embodiment, since the apparatus has a plurality of link information storage sections, and the reference information determination unit 3106 and extraction condition setting unit 3107, which specify information storage sections that are to undergo extraction, and can replace the current value by newly obtained link information, when an extraction condition has been changed, only a changed portion can be corrected. On the other hand, when new link information is added or deleted, a link information storage section can be added or deleted, and a corresponding portion can be added or deleted to or from the extraction condition. In this manner, link information which has a high degree of freedom and can reduce the number of data can be provided.

Since link information can be provided by only the change, even when a condition required for data search has been changed, link information can be provided without changing a program source.

As described above, according to the printer driver of this embodiment, when the extraction condition has been changed, only that portion can be corrected. Also, when new link information is added or deleted, a link information storage section can be added or deleted, and a corresponding portion can be added or deleted to or from the extraction condition. In this manner, link

information which has a high degree of freedom and can
reduce the number of data can be provided.

[Seventh Embodiment]

When a document or image is output to a printer on
5 an operating system (OS) for personal use, a printer
driver that matches the printer model must be used. The
printer driver offers various kinds of unique
information and data conversion functions for the
corresponding printer to the OS and application as the
10 calling side.

Such information includes paper margin information.
The paper margin information mainly includes four values,
i.e., the left margin, top margin, horizontal printable
area value, and vertical printable area value, as shown
15 in Fig. 52. The left margin specifies the distance from
the left end of a paper sheet to the left end of an area
to be actually printed. The top margin specifies the
distance from the top end of the paper sheet to the top
end of the area to be actually printed. The horizontal
20 and vertical printable area values are respectively
actually printable horizontal and vertical lengths. Upon
receiving these four pieces of information from the
driver, an application can generate accurate print data
so that data fall within the range defined by these
25 margins.

A margin information offering system according to the present invention will be described below with reference to the accompanying drawings.

Fig. 48 shows the arrangement according to the embodiment of the present invention. Fig. 48 extracts blocks that pertain to margin setups in a print process on the general OS. Reference numeral 4801 denotes an application program such as a wordprocessor, rendering software, or the like; and 4802, a printer driver. The printer driver 4802 offers margin information as one printer-dependent information to the application program. Reference numeral 4803 denotes a margin information offering unit according to the present invention.

When the printer driver 4802 offers margin information to the application program 4801, the printer driver 4802 itself calls this margin information offering unit 4803 to acquire its information.

This margin information offering unit 4803 comprises two blocks, i.e., a margin information generator (4803-1) and margin information table (4803-2). The margin information generator 4803-1 generates a left margin, top margin, and vertical and horizontal printable area values. The margin information table 4803-2 stores data required for the margin information generator 4803-1 to generate margin information in the form of table.

The table is stored in a normal file format, and includes two kinds of tables, i.e., index and data tables. The data table stores paper sizes and corresponding various margin values. The index table
5 stores the setup conditions of the printer driver, and IDs of data tables that store margin information which match those conditions. The margin information generator acquires a required table data ID from the index table in accordance with the setups of the printer driver, and
10 searches the data table designated by that ID, thus acquiring margin information.

A printer and the printer driver 4802 in this embodiment supports A4, A5, B5, envelope, and postcard sizes as paper sizes, and the user can select ON/OFF of
15 continuous paper and ON/OFF of perforated paper as special functions from the user interface on the driver. "Continuous paper" is special one in which sheets having a given size are continuously connected, and has top and bottom margins of 0 mm. "Perforated paper" is special
20 one, whose upper, lower, right, and left end portions are perforated, and which is used to print on full paper size by separating the perforated end portions after print is done on a range defined by perforations. When continuous paper = ON is selected, perforated paper is
25 unselectable, and margin values dedicated to continuous paper are set in correspondence with respective paper

09597403-052100
5 sizes. Likewise, when perforated paper can be selected and ON is selected, margin values dedicated to perforated paper are set in correspondence with respective paper sizes. In this manner, margin setups change depending on a setup item selected by the user.

Fig. 49 shows the flow of a margin information offering process according to the present invention.

10 In step S4901, parameters from the calling side (printer driver in this embodiment) are received. The received parameters include vertical and horizontal paper sizes, a paper size code obtained by coding the paper sizes, and ON/OFF information of continuous paper or perforated paper as a print condition.

15 The flow advances to step S4902, and the index table is loaded from the margin information table onto a memory. Note that an index table 5001 has a structure, as shown in Fig. 50. This table 5001 stores setup values of the printer driver and the IDs of data tables that store corresponding margin information. In Fig. 50, when
20 the setup of continuous paper is ON, a data table with ID = 100 is referred to; when the setup of continuous paper is OFF and that of perforated paper is ON, a table with ID = 110 is referred to; and when the setups of both continuous paper and perforated paper are OFF, a
25 table with ID = 120 is referred to. Note that "ALL" in Fig. 50 matches all states. The index table describes

conditions associated with all margin setups, and includes at least one table ID that matches every setups.

In step S4903, the index table loaded onto the memory is searched on the basis of items of the print
5 condition obtained in step S4901 to acquire the ID of a data table that matches the print condition.

In step S4904, the data table with the ID acquired in step S4903 is loaded onto the memory. Data tables with respective table IDs have structures shown in
10 Figs. 51A, 51B, and 51C. Note that the unit of each margin value is 1/100 mm. Data tables 5101 to 5103 store paper sizes, and left and top margins and vertical and horizontal printable area values corresponding to these sizes. For example, in the table 5101 with ID = 100,
15 A4-size paper has a left margin = 340, top margin = 0, horizontal printable area value = 20320, and vertical printable area value = 29700. In case of a user-defined size, a maximum horizontal printable area value is set in place of the horizontal printable area value, and a
20 bottom margin value is set in place of the vertical printable area value.

The flow advances to step S4905, and the data table loaded onto the memory in step S4904 on the basis of the paper size code acquired in step S4901 to obtain
25 a top margin, left margin, and vertical and horizontal printable area values. Only when the user-defined size

is selected, the maximum horizontal printable area value and bottom margin value are obtained in place of the vertical and horizontal printable area values.

It is checked in step S4906 if the paper size code
5 obtained in step S4901 means a user-defined size. If YES in step S4906, the flow advances to step S4907; otherwise (NO in step S4906), the flow advances to step S4908.

In step S4907, the respective margin values of the
10 user-defined size are computed. Since the vertical and horizontal printable area values change depending on the actual size values obtained in step S4901 for only the user-defined size, the margin values must be computed. The vertical and horizontal printable area values are
15 computed using the values obtained in step S4905 by:

Horizontal printable area value = horizontal size
of paper - (left margin value) \times 2

If horizontal printable area value > maximum
printable area value, the maximum printable area value
20 is used as the horizontal printable area value.

Vertical printable area value = vertical size of
paper - (top margin value) - (bottom margin value)

In step S4908, the left and top margins and
vertical and horizontal printable area values determined
25 in step S4905 or S4907 are returned to the calling side, thus ending the process.

With the aforementioned process, margin information is offered to the printer driver.

In this embodiment, tables are stored using a file system. However, the implementation method of the tables is not particularly limited as long as the tables and programs are separated. Also, even when a program is written in a ROM or the like as hardware, since the effects of the present invention remain the same, the present invention is not limited to a program format.

As described above, according to the printer driver of this embodiment, margin information is stored in a table file, and a program and data of margin information generation means are separated to use a common program, thus easily adding and changing the paper size.

For each printer, a table file is created for that model, thus improving the development efficiency.

Since two kinds of tables, i.e., index and data tables are used, even when complicated conditions are given, easy search and generation of margin information can be achieved without modifying the program of the margin information generation means.

[Another Embodiment]

Note that the present invention may be applied to either a system constituted by a plurality of devices (e.g., a host computer, an interface device, a reader, a

printer, and the like), or an apparatus consisting of a single equipment (e.g., a copying machine, a facsimile apparatus, or the like).

0012200" 00422560

The objects of the present invention are also
5 achieved by supplying a storage medium (or recording medium), which records a program code of a software program that can implement the functions of the above-mentioned embodiments to the system or apparatus, and reading out and executing the program code stored in
10 the storage medium by a computer (or a CPU or MPU) of the system or apparatus.

In this case, the program code itself read out from the storage medium implements the functions of the above-mentioned embodiments, and the storage medium
15 which stores the program code constitutes the present invention. The functions of the above-mentioned embodiments may be implemented not only by executing the readout program code by the computer but also by some or all of actual processing operations executed by an OS
20 (operating system) running on the computer on the basis of an instruction of the program code.

Furthermore, the functions of the above-mentioned embodiments may be implemented by some or all of actual processing operations executed by a CPU or the like
25 arranged in a function extension board or a function extension unit, which is inserted in or connected to the

computer, after the program code read out from the storage medium is written in a memory of the extension board or unit.

When the present invention is applied to the
5 storage medium, the storage medium stores program codes corresponding to the aforementioned flow charts (shown in Figs. 7 to 10, 13, 25 to 27, 30, 38, 39, and 49).

As many apparently widely different embodiments of the present invention can be made without departing from
10 the spirit and scope thereof, it is to be understood that the invention is not limited to the specific embodiments thereof except as defined in the appended claims.

09597403-062400